



Security level: Class S2 according to EN 14450
Security level: B according to VDMA 24992 - Conditions May'95

Suitable for the storage of:
 office documents, office equipment
 keys

Description
 Beckum series - furniture safes.

Body: double-walled body (60 mm thick)
Door: double-walled door construction (60 mm thick)
Locking: 4-way locking bolt system

Standard option
Lock: high security key lock I class VdS with two keys (65 mm)
Boltwork handle: knob, protruding 12 mm
Hinges: internal
Door opening angle: 90°
Mounting holes: 2 holes in the floor and in backwall
Colour: RAL 7035 (light grey)



Art. No.	Model	Outer dimensions*			Inner dimensions			Door light		Anchoring		Weight Kg	Shelves Number	Files Number	Volume Liters
		Height mm	Width mm	Depth mm	Height mm	Width mm	Depth mm	Height mm	Width mm	Bottom number	Backwall number				
35000	Beckum	465	500	430	345	368	301	315	295	2	2	200	1	4	38
35001	Beckum	665	500	430	545	368	301	515	295	2	2	200	2	4	60
35002	Beckum	865	500	430	745	368	301	715	295	2	2	200	2	8	83
35003	Beckum	990	500	430	870	368	301	840	295	2	2	200	2	8	96
35004	Beckum	665	500	430	545	368	301	515	295	2	2	300	2	4	60
35005	Beckum	865	500	430	745	368	301	715	295	2	2	300	2	8	83
35006	Beckum	990	500	430	870	368	301	840	295	2	2	300	3	8	96
35007	Beckum	1300	500	430	1180	368	301	1150	295	2	2	300	3	12	131
35008	Beckum	1600	500	430	1480	368	301	1450	295	2	2	300	3	16	164

* excluding hinges, handles and fittings



Body: double-walled body 60 mm thick




Door: double-walled door construction 60 mm thick

Closure options




Standard option




Key lock

Options available against surcharge



Mechanical code lock



Electronic lock




Electronic lock with mechanical emergency


Accessories available against surcharge



Left door



Inner safe (Excl. art 35000)



Shelf



RAL 7035



RAL 9006



RAL 7024

All information concerning weight, color and dimensions are noncommittal and subject to errors and changes. Minor deviations are conditional on the production process. Technical changes, modifications and printing errors reserved. Safes may be top-heavy, during commissioning, please exercise appropriate caution in accordance with the installation guide. Pictograms are not technical description of the product.