INTER SICHERHEITS SERVICE

Model
Amsterdam-Schiphol





Security level: Class V according to EN 1143-1
Fire rating: Fire-protected safes according to EN 15659 LFS 30 P

In order to save the fire-resistance certificate, the door should be built in the wall strictly according to the mounting manual instruction.

Descritpion:
Amsterdam-Schiphol series - strongroom door, burglar - proof.

Door: multi-walled door construction (145 mm thick)
Door frame: double-walled (78 mm thick)
Locking: 3-way locking bolt system - incl. overlaping profile on the hinge side

Standard option:
Lock: high security key lock VdS II class with two keys (170 mm), one of them folding key and mechanical emergency lock VdS II class
Boltwork handle: handle protruding 60 mm
Hinges: external
Door opening angle: 180°
Mounting holes: 10 holes, 4 in each side and 2 in the top
Colour: RAL 7035 (light grey)



Strongroom doors

Model
Amsterdam-Schiphol

Art. No.	Model	Outer dimensions* Height mm	Outer dimensions* Width mm	Outer dimensions* Depth mm	Door light Height mm	Door light Width mm	Anchoring Left Side number	Anchoring Right Side number	Anchoring In the top number	Weight Kg
55460	Amsterdam Schiphol	1700	900	300	1574	708	4	4	2	710
55461	Amsterdam Schiphol	1800	900	300	1674	708	4	4	2	746
55462	Amsterdam Schiphol	2000	1000	300	1874	808	4	4	2	878

* excluding hinges, handles and fittings

Door frame: double-walled (78 mm thick)

Door: multi-walled door construction (145 mm thick)

Closure options

Standard option

Options available against surcharge



Key lock and mechanical code lock



Mechanical code lock



Electronic lock

Accessories available against surcharge



Inner blockage



Additional inside handle



Additional keypad for inside lock



Alarm system elements/ Alarm system

RAL 7035

RAL 9006

RAL 7024

All information concerning weight, color and dimensions are noncommittal and subject to errors and changes. Minor deviations are conditional on the production process. Technical changes, modifications and printing errors reserved. Safes may be top-heavy, during commissioning, please exercise appropriate caution in accordance with the installation guide. Pictograms are not technical description of the product.

Strongroom doors