



Lukasiewicz Research Network
INSTITUTE OF PRECISION MECHANICS
CERTIFICATION DEPARTMENT

01-796 Warszawa, ul. Duchnicka 3

phone 22 663-43-24, 22 560-28-00 e-mail: certyfikacja.imp@imp.edu.pl
<http://www.imp.edu.pl>



AC 041

CERTIFICATE OF CONFORMITY

No. P41/094/2019 (7738)

ENGLISH EDITION

Name and address of the certificate owner:

INTER SICHERHEITS SERVICE Sp. z o. o.
66-400 GORZÓW WLKP., ul. Kobylogórska 2

Name and address of the manufacturer:

INTER SICHERHEITS SERVICE Sp. z o. o.
66-400 GORZÓW WLKP., ul. Kobylogórska 2

Product name:

Safe for storage of valuables

Type (variants):

Dresden, Dresden-Schönefeld, Dresden-Coswig, Dresden-Radebeul, Dresden-Carbo

Detailed information about dimensions and masses on the reverse of the certificate

Main features:

Product class: - I -

The product fulfills requirements of:

PN-EN 1143-1:2012

Date of expiration: **May 28, 2022**

This certificate is valid from **May 29, 2019** until **May 28, 2022** only for products covered by application No. 054/W/2019, provided that the technical specification is valid, item fulfills its requirements and there were no major changes in: product type, system, conditions and the place of the production.

Certification of conformity Type „3” acc. to PN-EN ISO/IEC 17067: 2014-01.

Certificate of conformity issued acc. to the program PC-01 (IMP)

MANAGER
CERTIFICATION DEPARTMENT


Marek ZIĘTALA M.Sc. Eng.



DIRECTOR OF THE INSTITUTE


Tomasz BABUL Ph.D. D.Sc. Eng. prof. IMP

Certificate can be published only by Certificate Owner without comments, abbreviations and changes.
Warsaw, May 29, 2019.

No P41/094/2019 (7738)

Dresden, Dresden-Schönefeld, Dresden-Coswig, Dresden-Radebeul, Dresden-Carbo safes (class I acc. to PN-EN 1143-1:2012) - basic parameters

| Outer dimensions (mm) | | | Mass |
|-----------------------|-------|-------|------|
| height | width | depth | kg |
| 514 | 604 | 400 | 95 |
| 606 | 636 | 510 | 129 |
| 806 | 636 | 510 | 164 |
| 906 | 636 | 510 | 182 |
| 1006 | 636 | 510 | 198 |
| 1206 | 636 | 510 | 239 |
| 1506 | 806 | 550 | 305 |
| 1806 | 806 | 550 | 345 |
| 800 | 700 | 550 | 197 |
| 1250 | 700 | 550 | 285 |
| 1500 | 700 | 550 | 345 |
| 1950 | 700 | 550 | 380 |
| 1950 | 950 | 550 | 495 |
| 1950 | 1260 | 550 | 595 |
| 1806 | 1486 | 550 | 660 |
| 1006 | 736 | 600 | 215 |
| 1256 | 836 | 600 | 280 |
| 1506 | 836 | 600 | 350 |
| 1806 | 836 | 600 | 425 |
| 1806 | 1200 | 800 | 625 |

Allowed sizes:

Height: from 500 to 2000 mm

Width: from 500 to 1200 mm 1 door

from 800 to 1500 mm 2 doors

Depth: from 350 to 1000 mm

KIEROWNIK
Zakładu Certyfikacji


mgr inż. Marek Zietala