

Model
Paris-Versailles



Security level: Class II according to EN 1143-1
Fire rating: Fire-protected inner safe according to EN 1047-1 S60DIS

Suitable for the storage of:
 office documents, office equipment
 valuables

Description
 Paris-Versailles series - High security safes with inner safe with one-hour protection from fire S 60 DIS.

Body: multi-walled body (52 mm thick)
Door: multi-walled door construction (109 mm thick)
Locking: 4-way locking bolt system - incl. overlapping profile on the hinge side


Standard option
Lock: high security key lock I class VdS with two keys (145 mm)
Boltwork handle: handle, protruding 60 mm
Hinges: external
Door opening angle: 180°
Mounting holes: 2 holes in the floor
Colour: RAL 7035 (light grey)



Model
Paris-Versailles

Art. No.	Model	Outer dimensions*			Inner dimensions			Anchoring		Weight Kg	Drawers Number	Volume Liters
		Height mm	Width mm	Depth mm	Height mm	Width mm	Depth mm	Bottom number	Backwall number			
46800	Paris-Versailles	779	684	815	675	568	651	2	-	740	3	59
46801	Paris-Versailles	779	684	950	675	568	786	2	-	815	3	79
46802	Paris-Versailles	1079	684	815	975	568	651	2	-	880	3	59
46803	Paris-Versailles	1079	684	950	975	568	786	2	-	950	3	79
46804	Paris-Versailles	1414	684	815	1310	568	651	2	-	1220	2 x 3	118
46805	Paris-Versailles	1414	684	950	1310	568	786	2	-	1290	2 x 3	159
46806	Paris-Versailles	1714	684	815	1610	568	651	2	-	1315	2 x 3	118
46807	Paris-Versailles	1714	684	950	1610	568	786	2	-	1395	2 x 3	159

* excluding hinges, handles and fittings



Closure options



Accessories available against surcharge



All information concerning weight, color and dimensions are noncommittal and subject to errors and changes. Minor deviations are conditional on the production process. Technical changes, modifications and printing errors reserved. Safes may be top-heavy, during commissioning, please exercise appropriate caution in accordance with the installation guide. Pictograms are not technical description of the product.