

Model
Wismar



The product adjusted to be build or to be anchored in the wall. Handle and lock on both sides of door.

Descritpion:
Wismar series - burglar - proof door.

Door: double-walled door construction (62 mm thick)
Door frame: double-walled (32 mm thick)
Locking: 3-way locking bolt system.

Standard option:
Lock: Double cylinder lock
Boltwork handle: handle, protruding 60 mm
Hinges: external
Door opening angle: 180°
Mounting holes: 6 holes, 3 in each side
Colour: RAL 7035 (light grey)



Model
Wismar

Art. No.	Model	Outer dimensions*			Door light		Anchoring			Weight Kg
		Height mm	Width mm	Depth mm	Height mm	Width mm	Left Side number	Right Side number	In the top number	
32300	Wismar	2000	750	120	1936	686	3	3	0	81
32301	Wismar	2000	750	240	1936	686	3	3	0	93
32302	Wismar	2000	830	120	1936	766	3	3	0	86
32303	Wismar	2000	830	240	1936	766	3	3	0	98
32304	Wismar	2000	1000	120	1936	936	3	3	0	95
32305	Wismar	2000	1000	240	1936	936	3	3	0	108

* excluding hinges, handles and fittings



Door frame: double-walled
(32 mm thick)



Door: double-walled door
construction (62 mm thick)

Closure options

Standard option



Double cylinder lock

Options available against surcharge



Electronic lock



Electronic lock with mechanical
emergency opening

Accessories available against surcharge



Additional keypad for
inside lock



RAL
7035



RAL
9006



RAL
7024



All information concerning weight, color and dimensions are noncommittal and subject to errors and changes. Minor deviations are conditional on the production process. Technical changes, modifications and printing errors reserved. Safes may be top-heavy, during commissioning, please exercise appropriate caution in accordance with the installation guide. Pictograms are not technical description of the product.