INTER SICHERHEITS SERVICE

Model
Solingen





Security level: Class S2 according to EN 14450/ VdS 2862
Fire rating: Fire-protected safes according to EN 1047-1 S 60 P

The cabinet has been approved in accordance with EN 1047-1 in fire class 60 P. The certification was awarded by VdS they have fire and impact tests.

Suitable for the storage of:
- **office documents, office equipment**

Description
Series Solingen - the cabinets with one hour protection from fire S 60 P.

Body: double-walled body (50 mm thick)
Door: multi-walled door construction (95 mm thick)
Locking: 4-way locking bolt system - incl. fix bolts on the hinge side

Standard option
Lock: high security key lock I class with two keys (120 mm)
Boltwork handle: handle, protruding 60 mm
Hinges: external
Door opening angle: 180°
Mounting holes: 2 holes in the floor
Colour: RAL 7035 (light grey)



Model
Solingen

Art. No.	Model	Outer dimensions*			Inner dimensions			Door light		Anchoring		Weight	Shelves	Files	Volume
		Height mm	Width mm	Depth mm	Height mm	Width mm	Depth mm	Height mm	Width mm	Bottom number	Backwall number	Kg	Number	Number	Liters
39400	Solingen	380	463	440	279	351	298	264	328	2	-	105	1	3 **	29
39401	Solingen	440	463	440	339	351	298	324	328	2	-	115	1	4	35
39402	Solingen	615	463	440	515	351	298	499	328	2	-	145	1	6	54
39403	Solingen	775	463	440	674	351	298	659	328	2	-	165	2	8	70
39404	Solingen	1137	704	471	1036	592	329	1021	569	2	-	330	2	21	202
39405	Solingen	1322	704	471	1221	592	329	1206	569	2	-	365	3	23	238
39406	Solingen	1507	704	471	1406	592	329	1391	569	2	-	395	3	28	274

* excluding hinges, handles and fittings ** crosswise

Body: double-walled body 50 mm thick

Door: multi-walled door construction 95 mm thick

Closure options

Standard option



Key lock

Options available against surcharge



Mechanical code lock

Electronic lock

Electronic lock with mechanical emergency (Excl. 39400-39403)

Accessories available against surcharge



Inner safe

Extensible file frame

Extendable shelf

Extendable drawer for individual arragement

Shelf for hanging files

RAL 7035

RAL 9006

RAL 7024

All information concerning weight, color and dimensions are noncommittal and subject to errors and changes. Minor deviations are conditional on the production process. Technical changes, modifications and printing errors reserved. Safes may be top-heavy, during commissioning, please exercise appropriate caution in accordance with the installation guide. Pictograms are not technical description of the product.

Fireproof Safes for Paper Documents