INTER SICHERHEITS SERVICE

Model
Solingen Super





Security level: Class S2 according to EN 14450/ VdS 2862
Fire rating: Fire-protected safes according to EN 1047-1 S 60 P

The cabinet has been approved in accordance with EN 1047-1 in fire class 60 P. The certification was awarded by VdS they have fire and impact tests.

Suitable for the storage of:
- **office documents, office equipment**

Description
Series Solingen Super - the cabinets with one-hour protection from fire S 60 P.

Body: double-walled body (50 mm thick)
Door: multi-walled door construction (95 mm thick)
Locking: 4-way locking bolt system - incl. fix bolts on the hinge side

Standard option
Lock: high security key lock I class with two keys (120 mm)
Boltwork handle: handle, protruding 60 mm
Hinges: external
Door opening angle: 180°
Mounting holes: 2 holes in the floor
Colour: RAL 7035 (light grey)



Model
Solingen Super

Art. No.	Model	Outer dimensions* Height mm	Outer dimensions* Width mm	Outer dimensions* Depth mm	Inner dimensions Height mm	Inner dimensions Width mm	Inner dimensions Depth mm	Door light Height mm	Door light Width mm	Anchoring Bottom number	Anchoring Backwall number	Weight Kg	Shelves Number	Files Number	Volume Liters
39450	Solingen Super	1550	886	545	1449	774	403	1434	751	1	-	509	3	40	452
39452	Solingen Super	1700	886	545	1599	774	403	1584	751	1	-	547	4	44	499
39454	Solingen Super	1884	886	545	1783	774	403	1768	751	1	-	605	4	50	556
39457	Solingen Super **	1884	975	559	1783	863	393	1768	845	1	-	701	4	55	605
39458	Solingen Super **	1884	975	696	1783	863	530	1768	845	1	-	795	4	55	816
39460	Solingen Super **	1884	1128	559	1783	1016	393	1768	998	1	-	790	4	65	712
39461	Solingen Super **	1884	1128	696	1783	1016	530	1768	998	1	-	851	4	65	960
39462	Solingen Super **	1884	1282	459	1783	1170	293	1768	1152	1	-	839	4	75	611
39463	Solingen Super **	1884	1282	559	1783	1170	393	1768	1152	1	-	886	4	75	820
39464	Solingen Super **	1884	1282	696	1783	1170	530	1768	1152	1	-	951	4	75	1106

* excluding hinges, handles and fittings ** 2-door



Body: double-walled body 50 mm thick



Door: multi-walled door construction 95 mm thick

Closure options

Standard option



Key lock

Options available against surcharge



Mechanical code lock



Electronic lock



Electronic lock with mechanical emergency (Excl. 39456-39458)


Accessories available against surcharge




Inner safe




Inner safe with partition wall, 2 - door




Extensible file frame



Extendable shelf



Extendable drawer for individual arragement



Shelf for hanging files



Floppy disk insert S60DIS

RAL 7035

RAL 9006

RAL 7024

All information concerning weight, color and dimensions are noncommittal and subject to errors and changes. Minor deviations are conditional on the production process. Technical changes, modifications and printing errors reserved. Safes may be top-heavy, during commissioning, please exercise appropriate caution in accordance with the installation guide. Pictograms are not technical description of the product.